

DATASHEET-FIBER OPTIC SPLICE CLOSURE(INLINE TYPE)&FIBER ACCESS TERMINAL CLOSURE



							
Product Number	FCST01159	FCST01182	FCST01120	FCST01173	FCST01160	FCST01105	FCST01157
Max. Capacity	24cores(Branch: 8 cores)	24cores(Branch: 16 cores)	36cores	48cores	48cores	48cores	72cores
Dimension (mm)	182*272*72	605*168*90	295*220*90	340*150*70	250*185*95	485*171*108	490*200*120
Inlets/Outlets	2/2	4/4	2/2	2/2	4/4	2/2	2/2
Installation	Pole/Wall/Aerial	Pole/Wall/Aerial	Pole/Aerial/manhole	Pole/Aerial/manhole	Pole/Wall/Aerial	Pole/Aerial/manhole	Pole/Aerial/manhole
Protection Level	IP55	IP65	IP68	IP68	IP65	IP67	IP68

DATASHEET-FIBER OPTIC SPLICE CLOSURE(INLINE TYPE)&FIBER ACCESS TERMINAL CLOSURE



Product Number	FCST01166-B	FCST01136	FCST01103	FCST01176	FCST01147	FCST01108	FCST01178
Max. Capacity	72/144cores(Branch:16cores)	96cores	96cores	144cores	180cores	288cores	288cores
Dimension (mm)	230*510*150	285*175*90	405*158*145	457*201*120	648*254*158	450*220*160	556*258*156
Inlets/Outlets	2/2	3/3	3/3	4/4	3/3	3/3	4/4
Installation	Pole/Aerial/manhole	Pole/Aerial/manhole	Pole/Aerial/manhole	Pole/Aerial/manhole	Pole/Aerial/manhole	Pole/Aerial/manhole	Pole/Aerial/manhole
Protection Level	IP68	IP65	IP68	IP68	IP68	IP68	IP68

DATASHEET-FIBER OPTIC SPLICE CLOSURE(INLINE TYPE)&FIBER ACCESS TERMINAL CLOSURE



Product Number	FCST01131-A	FCST01131-B	FCST01131-C	FCST01131-D	FCST01133-A	FCST01133-B	FCST01133-C
Max. Capacity	8Cores	8Cores	8Cores	8Cores	8Cores	8Cores	8Cores
Dimension (mm)	155*235*50	155*235*50	156*232*53.2	156*185*53.5	266*237*75	266*237*75	266*237*75
Inlets/Outlets	2/8	2/8	2/8	2/8	4/8	4/8	4/8
Installation	Pole/Wall/Aerial	Pole/Wall/Aerial	Pole/Wall/Aerial	Pole/Wall/Aerial	Pole/Aerial/manhole	Pole/Aerial/manhole	Pole/Aerial/manhole
Protection Level	IP65	IP65	IP65	IP65	IP67	IP67	IP67
Remark	cable sealing terminations use gel-sealing technology instead of Plain rubber seal.						

DATASHEET-FIBER OPTIC SPLICE CLOSURE(INLINE TYPE)&FIBER ACCESS TERMINAL CLOSURE



FCST01135 Fiber Access Terminal Closures

REMARK: cable sealing terminations use **gel-sealing technology** instead of Plain rubber seal.

Construction	Description
Capacity Of FOSC(Bunchy)	66 cores
Max. Capacity	8cores(SC/APC)
Material	PP
Dimension (mm)	336.5*195*128
Inlets/Outlets	4/8
Installation	Pole mounting, Pedestal mounting Strand mounting, Wall-mounting
Net Weight(g)	2050
Protection Level	IP67